

# 3d Brain Atlas Reconstructor on-line service

## getReconstruction

Returns a model of a given structure from selected dataset as a zip file containing the reconstruction and short description.

syntax

```
getReconstruction?cafDatasetName=<dataset name>  
                ;structureName=<structure name>  
                [;qualityPreset=(low|high)]  
                [;outputFormat=(vrml|niftii)]
```

### Required arguments

- cafDatasetName

The service identifier of the selected CAF dataset.

- structureName

Name of structure from hierarchy tree. In practice nearly all names should be fine. Formally name has to point to a root node of a subtree containing at least one node with representation among paths in CAF slides.

### Optional arguments

- qualityPreset

Sets predefined quality preset. Possible values are 'low' and 'high', the default value is 'low'.

- outputFormat

Defines format of the reconstruction. Possible values are 'vrml' and 'niftii', the default value is 'vrml'.

### Examples

- [http://service.3dbar.org/getReconstruction?cafDatasetName=whs\\_0.51;structureName=thalamus](http://service.3dbar.org/getReconstruction?cafDatasetName=whs_0.51;structureName=thalamus)
- [http://service.3dbar.org/getReconstruction?cafDatasetName=whs\\_0.51;structureName=thalamus;qualityPreset=high](http://service.3dbar.org/getReconstruction?cafDatasetName=whs_0.51;structureName=thalamus;qualityPreset=high)